



DIY ZIPPER BOX BAG TUTORIAL




Step-by-Step Sewing Guide



MATERIALS

- Main fabric (quilt cotton): 40 cm
- Lining fabric: 40 cm
- Fusible interfacing (medium): 40 cm
- 1 Zipper (nylon) – 45 cm
- 1 Zipper pull x 2
- Matching thread
- Fabric scissors
- Sewing clips or pins
- Ruler, marking pen
- Iron and sewing machine

FINISHED SIZE



FABRIC CUTTING (all measurements include 1 cm seam allowance)


TOP & BOTTOM

Cut 2 (Main fabric)




FRONT & BACK

Cut 2 (Main fabric)



SIDE PANELS

Cut 2 (Main fabric)



LINING (repeat all pieces)

Cut the same as main fabric



HANDLE

Cut 1 (Main fabric)




ZIPPER TABS (optional)

Cut 2 (Main fabric)



1 INTERFACING



Iron fusible interfacing to the wrong side of all main fabric pieces (except handle and zipper tabs).

2 MAKE THE HANDLE



Fold the handle strip in half lengthwise, right sides together. Stitch along the long edge. Turn right side out and topstitch along both long edges.

3 ATTACH HANDLE



Center the handle on the top piece. Place ends 6 cm from the side edges. Pin or clip in place. Sew a rectangle with an X on each end to secure.

4 SIDE PANELS



Sew the side panels to the front and back pieces. Repeat for the other side. Press seams open.

5 BOX SHAPE



Your bag body should now look like a box.

6 ATTACH TOP



Pin the top piece to the top edge of the bag. Sew all around. Repeat to attach the bottom piece.

7 PREPARE ZIPPER



Open the zipper and place it right sides down on the top edge. The zipper pull should be in the middle. Pin or clip.

8 SEW ZIPPER



Using a zipper foot, sew along the zipper teeth. Repeat for the other side of the top with the remaining zipper tape.

9 FINISH ZIPPER ENDS



Attach the zipper tabs (optional): Fold tab in half, stitch across short ends. Slide the tab onto the zipper end and stitch in place.

10 REPEAT FOR LINING



Sew the lining pieces in the same way, but leave a 10 cm opening in the bottom for turning.

11 JOIN LINING & BAG



Place lining inside the bag, wrong sides together. Match top edges and pin. Sew all around.

12 TURN & CLOSE



Turn the bag right side out through the opening. Push out corners. Hand stitch the opening closed.

13 TOPSTITCH



Topstitch all around the top edge for a clean finish and to keep the lining in place.

14 DONE!



Your Zipper Box Bag is ready to use! Perfect for cosmetics, sewing notions, or travel.

TIPS

- ♥ Use quilting cotton from the USA for best results.
- ♥ Press seams as you go for a professional finish.
- ♥ A longer zipper works best for easy opening.
- ♥ Customize the size by adjusting the measurements.

MAIN SEWING TECHNIQUES USED

Seam Allowance

All pieces include 1 cm seam allowance.

Topstitching

Topstitching on the right side to reinforce and decorate.

Boxed Corners

Creating a 3D shape by sewing flat pieces together.

Zipper Installation

Sewing a zipper between fabric layers for a strong finish.

Turning

Turning the project right side out through an opening.

Edge Finishing


Topstitching ensures durability and a clean look.

FABRIC RECOMMENDATION (USA)

- Quilting Cotton
- Canvas or Denim (for a sturdier bag)
- Oilcloth or Waterproof Fabric (for easy cleaning)



<https://creative.craftsforlove.com/> - SEE THE BEST PATTERNS



<https://creative.craftsforlove.com/> - SEE THE BEST PATTERNS

DIY Zipper Box Bag Tutorial – Step-by-Step Sewing Guide

This DIY Zipper Box Bag is a practical sewing project that creates a structured rectangular bag with a zipper closure, a sturdy carrying handle, and a fully finished lining. The completed bag is ideal for cosmetics, sewing notions, craft supplies, toiletries, or travel essentials.

This tutorial follows the measurements, construction order, and techniques shown in the original sewing guide. All

measurements are given in centimeters, and the pattern pieces include a 1 cm seam allowance unless otherwise stated.

The approximate finished size is 24 cm wide × 12 cm deep × 14 cm high, or about 9 1/2 × 4 3/4 × 5 1/2 inches.



Materials and Supplies

Before beginning, gather all of your fabrics, notions, and sewing tools.

You will need:

- 40 cm main fabric, preferably quilting cotton
- 40 cm lining fabric
- 40 cm medium-weight fusible interfacing
- 1 nylon zipper, 45 cm long
- 2 zipper pulls
- Matching sewing thread
- Fabric scissors or rotary cutter
- Sewing clips or pins
- Ruler
- Fabric marking pen or pencil
- Iron and ironing board
- Sewing machine
- Zipper foot for your sewing machine

For the main fabric, quilting cotton is an excellent choice because it is easy to sew and produces a neat finished bag.

If you prefer a sturdier bag, canvas or denim can also be used. For a bag that will hold cosmetics or toiletries, an oilcloth or waterproof fabric can be useful because the surface is easier to wipe clean.



Fabric Cutting

All pattern measurements in this tutorial already include the 1 cm seam allowance.

Cut the pieces carefully and keep them organized before beginning construction.

Top and Bottom

Cut 2 pieces from the main fabric.

Each piece measures approximately:

24 cm × 12 cm

One will become the top portion of the bag and the other will form the bottom.

Front and Back

Cut 2 pieces from the main fabric.

Each piece measures:

24 cm × 14 cm

These two rectangles form the large front and back walls of the finished box bag.

Side Panels

Cut 2 pieces from the main fabric.

Each side panel measures:

12 cm × 14 cm

The side panels create the depth of the bag.

Handle

Cut 1 piece from the main fabric measuring:

30 cm × 5 cm

This strip will be folded and sewn to create the carrying handle.

Zipper Tabs

Cut 2 pieces from the main fabric measuring approximately:

4 cm × 4 cm

These small pieces are optional, but they give the zipper ends a cleaner and more professional appearance.

Lining

Cut the lining pieces in the same sizes as the corresponding main bag pieces so that the lining matches the exterior construction.

Keep the lining pieces separate from the exterior pieces while sewing to avoid mixing them up.

1. Apply the Fusible Interfacing

Begin by preparing the main exterior pieces.

Place each main fabric piece with its wrong side facing upward.

Cut fusible interfacing to fit the main bag pieces and position the adhesive side of the interfacing against the wrong side of the fabric.

Apply interfacing to the exterior bag pieces, except the handle and zipper tabs.

Follow the manufacturer's instructions for your particular interfacing because pressing temperature and pressing time may vary.

Instead of moving the iron continuously as you would when ironing clothing, press it firmly over one section for several seconds. Lift the iron and move to the next area.

Continue until the interfacing has completely fused to the fabric.

Allow each piece to cool before moving it. This helps the adhesive set properly.

The interfacing gives the finished zipper box bag more structure and helps it maintain its rectangular shape.

2. Make the Handle

Take the 30 cm × 5 cm handle strip.

Fold the strip in half lengthwise with the right sides of the fabric together.

Align the two long raw edges carefully.

Pin or clip the long edge to prevent the fabric from shifting.

Sew along the long edge using the appropriate seam allowance.

Leave both short ends open.

Turn the handle right side out.

A loop turner, safety pin, or blunt turning tool can make this easier.

Once the strip has been completely turned, arrange the seam neatly and press the handle flat.

Topstitch along both long edges of the handle.

Keep the stitching straight and evenly spaced from the edges.

Topstitching gives the handle a more polished appearance while also adding strength.

3. Attach the Handle

Take the main fabric piece that will become the top of the bag and place it right side up.

Position the handle over the center of this piece.

The handle should form an arch above the fabric rather than lying completely flat.

Position each end approximately 6 cm from the corresponding side edge, following the placement shown in the guide.

Make sure the handle is centered and that it is not twisted.

Pin or clip each end securely.

Sew a small rectangle at each handle end.

Then sew diagonally through the rectangle to create an X-shaped reinforcement.

Repeat at the opposite end.

This rectangle-and-X method distributes stress across a larger section of fabric and makes the handle considerably stronger.

Check that both ends are secure before moving to the next step.

4. Sew the Side Panels

Place one side panel against the edge of the front panel with right sides together.

Align the raw edges.

Pin or clip the pieces together.

Sew the seam using the included 1 cm seam allowance.

Attach the remaining side panel in the same way.

Next, connect the side panels to the back panel.

Work carefully to keep the upper and lower edges aligned.

After sewing, press the seams open whenever possible.

Pressing the seams as you work prevents unnecessary bulk and helps create crisp corners in the finished bag.

At this stage, the front, back, and side pieces should begin forming a rectangular tube.

5. Form the Box Shape

Arrange the sewn front, back, and side panels so the bag begins to resemble an open rectangular box.

Check each corner.

The seams should meet cleanly, and the top and bottom edges should remain reasonably even.

If necessary, pin or clip around the edges while checking the shape.

Avoid stretching the fabric at the corners.

Because the interfacing adds structure, the exterior should already begin holding its three-dimensional shape.

Make sure there are no accidental folds caught in the seams before continuing.

6. Attach the Top and Bottom Pieces

Take the prepared top piece with the handle attached.

With right sides together, position it against the upper edge of the bag body.

Match the edges and corners.

Pin or clip around the perimeter.

When working around the corners, use several clips or pins to keep the layers controlled.

Sew around the entire edge.

Work slowly at each corner so the stitching remains accurate.

Next, repeat the process with the bottom piece.

Place the bottom piece against the remaining open edge with right sides together.

Match the corners and raw edges.

Pin or clip securely and sew around the perimeter.

The exterior should now have the recognizable shape of a box bag.

7. Prepare the Zipper

Use the 45 cm nylon zipper specified in the materials list.

Open the zipper before beginning installation.

Position the zipper along the top opening according to the guide, with the zipper and fabric right sides facing together.

The zipper pull should be positioned approximately in the middle while you work.

This prevents the pull from interfering with the first stages of stitching.

Align the zipper tape carefully with the fabric edge.

Use sewing clips or pins to hold the zipper securely.

Because zipper tape can shift while sewing, place clips fairly close together.

Before stitching, check that the zipper is not twisted.

8. Sew the Zipper

Install a zipper foot on your sewing machine.

Position the project under the presser foot.

Sew close to the zipper teeth without allowing the needle to strike them.

Keep the zipper tape and fabric edges aligned as you sew.

When approaching the zipper pull, stop sewing with the needle down.

Lift the presser foot and carefully move the zipper pull out of the way.

Lower the presser foot and continue sewing.

After completing the first side, position the remaining zipper tape along the opposite top edge.

Again, keep the right sides correctly positioned.

Pin or clip it in place.

Sew the second zipper side using the same method.

Check the zipper after stitching.

It should open and close smoothly without catching the surrounding fabric.

9. Finish the Zipper Ends

The zipper tabs are optional, but they provide a clean finish.

Take one 4 cm × 4 cm zipper tab.

Fold it in half and position it across one short end of the zipper.

Arrange the raw edges neatly.

Slide the tab over the zipper end and stitch it securely in place.

Trim excessive bulk if necessary without cutting through your stitching.

Repeat at the other end of the zipper.

The fabric tabs help cover the raw zipper tape and give the project a more professionally finished appearance.

10. Sew the Lining

Construct the lining using the same general method used for the exterior.

Join the front, back, and side lining pieces with right sides together.

Sew the seams using the same 1 cm seam allowance.

Continue assembling the lining so its shape matches the exterior bag.

When attaching the bottom lining piece, leave an opening of approximately 10 cm along one seam.

Do not sew this opening closed yet.

The opening is extremely important because the entire project will later be turned right side out through it.

Backstitch securely at both ends of the opening.

This prevents the seam from coming undone while the bag is being turned.

Press the lining seams neatly.

11. Join the Lining and Exterior Bag

Place the lining with the exterior bag according to the construction shown in the guide.

Arrange the layers so the appropriate sides are facing one another and the top edges match.

Make sure the side seams of the lining line up with the side seams of the exterior.

Pin or clip around the complete upper edge.

Use extra clips near thicker areas, especially around the zipper ends and side seams.

Sew completely around the upper edge.

Take your time when sewing near the zipper.

Keep the zipper teeth away from the needle.

Once the seam is complete, inspect the stitching before turning the project.

If you see any gaps or areas where one layer was not caught in the seam, repair them now.

12. Turn the Bag and Close the Opening

Locate the 10 cm opening left in the bottom of the lining.

Carefully begin pulling the exterior bag through this opening.

Do not pull aggressively because the corners and zipper areas may be bulky.

Work gradually until the entire project has been turned right side out.

Push out all four corners.

A blunt turning tool can help define the corners, but avoid using scissors or another sharp object because it could puncture the fabric.

Once everything has been turned, smooth the exterior and lining with your hands.

Fold the raw edges of the 10 cm lining opening inward so they align with the sewn seam.

Press the fold.

Hand stitch the opening closed using small, neat stitches.

A ladder stitch or slip stitch is particularly useful because the stitches are nearly invisible.

After closing the opening, place the lining neatly inside the exterior bag.

13. Topstitch the Upper Edge

Arrange the lining inside the bag and press the upper edge carefully.

Make sure no lining fabric is sticking into the zipper teeth.

Topstitch around the entire upper edge.

Keep the stitching consistent and close to the seam.

This final row of topstitching serves several purposes.

It gives the bag a polished appearance, helps prevent the lining from shifting, reinforces the upper edge, and keeps the zipper area neat.

Move slowly around corners and bulky seam intersections.

After topstitching, remove any remaining loose threads.

14. Final Finishing ✨

Your DIY Zipper Box Bag is now complete.

Open and close the zipper several times to make sure it operates smoothly.

Check the handle by gently pulling upward on it.

Inspect the corners and seams for loose threads.

Push the corners into their final shape and arrange the lining evenly inside the bag.

If the fabric allows it, give the finished project a final light pressing.

Avoid placing a hot iron directly against plastic or nylon zipper teeth.

The completed bag should measure approximately 24 cm × 12 cm × 14 cm.

Its structured shape makes it useful for cosmetics, sewing supplies, small craft projects, toiletries, travel accessories, or everyday storage.

Important Sewing Techniques Used

A 1 cm seam allowance is included in the pattern measurements. Maintaining the same seam allowance throughout the project is important because variations can change the final dimensions and cause the lining and exterior to fit differently.

Topstitching means sewing a visible line of stitching on the right side of the project. In this bag, it reinforces the handle and upper edge while producing a more professional finish.

The boxed construction is created by joining rectangular front, back, side, top, and bottom pieces. Accurate seams and well-matched corners are essential for achieving the three-dimensional box shape.

For zipper installation, use a zipper foot and stitch close to the zipper teeth without sewing directly over them. Move the zipper pull when necessary instead of trying to force the presser foot around it.

Turning refers to pulling the completed exterior through the opening left in the lining so the right sides become visible. Always leave the recommended 10 cm opening so there is enough room to turn the structured bag safely.

Edge finishing and final topstitching help keep the lining in place, reinforce the zipper area, and create a clean finished appearance.

Tips for the Best Results

Use good-quality quilting cotton if you want a bag similar to the one shown in the tutorial. Press every seam as you work because pressing is one of the easiest ways to make a handmade bag look professionally constructed.

A slightly longer zipper is easier to work with than one that is exactly the finished length because the extra tape provides more room during installation.

For a firmer bag, choose medium-weight interfacing with enough body to support the fabric without making the seams excessively bulky.

If using denim or canvas, consider reducing bulk in seam allowances around corners and zipper ends.

If using waterproof material for the lining, use clips rather than pins whenever possible because pins may leave permanent holes.

Most importantly, keep the 1 cm seam allowance consistent, check the orientation of every piece before sewing, and verify that the zipper works properly before permanently joining the lining and exterior. These small checks make the final assembly much easier and help ensure that your finished Zipper Box Bag is neat, sturdy, and ready to use.

<https://creative.craftsforlove.com/> - **SEE THE BEST PATTERNS**